

Specialists in endoscope reprocessing
for more than 30 years!

WASSENBURG® WD440

Endoscope washer-disinfector

+ **NEW LED process identification**

Clear process identification through colour LED technology.

+ **NEW Intuitive colour touchscreen**

User-friendly: fast, safe and easy operation.

+ **NEW High-level ergonomics**

Hygienic one-touch opening by foot sensor.

+ **High capacity**

Independent double bay system for reprocessing 2 endoscopes separately.

+ **Optimum safety**

World-beating Wassenburg technology: individual channel connection combined with channel separation.



OPTIMUM CONTROL

- + Channel separation
- + Flow and pressure control
- + Tube connection control
- + Independent Monitoring System (IMS)
- + Leakage control
- + Blockage control
- + Traceability with Process Manager
(and upload possibility to third party programs)

DIMENSIONS AND WEIGHT


Width x Depth x Height: 941 x 750 x 1033 mm (1580 mm when lid open)
Weight when empty (approx.): 200 kg

ELECTRICAL CONNECTION

Voltage: 220 – 240 V (frequency 50Hz)
Type of electrical connection: plug with ground connection

WATER SUPPLY AND DRAIN

Min. / max. pressure: 2.5 / 4 bar (max. difference between hot and cold water supplies: 1 bar)
Minimum flow rate for hot / cold water supplies: 10 l/min (drain capacity: 20 l/min per drain)
Drain: 2 drains + 2 overflows, both overflow tubes will be shared in 1 drain (diameter per drain: > DN40)
Height of drain: 530 mm (+/- 5 mm)



Please contact us for the full installation specifications of the WASSENBURG® WD440.
The WASSENBURG® WD440 is CE-marked and fully compliant with EN ISO 15883 parts 1 and 4.
© Copyright 2015. Subject to alterations.

Wassenburg Medical B.V.
Edisonring 9
6669 NA DODEWAARD
THE NETHERLANDS

T: +31 (0) 488 700 500
F: +31 (0) 488 453 685
info@wassenburgmedical.nl
www.wassenburgmedical.com