

Specialists in endoscope reprocessing for more than 35 years!



Wassenburg Boiler

Offering a safe solution to supply consistent warm water for WASSENBURG® washer-disinfectors

WASSENBURG
medical

OPTIMUM SAFETY

All Wassenburg Boilers are made of the highest quality stainless steel and designed to supply consistent warm water for optimum performance with our WASSENBURG® washer-disinfectors. In case warm water cannot be provided by the hospital or private clinic.

The safe Wassenburg Boiler is compliant with the latest regulation and norms (Pressure Equipment and Low voltage Directive):

- BT 2014/35/EU (50 L Boiler), BT 2014/35/CE (150 L Boiler)
- EMC 2014/35/EU (50 L Boiler), EMC 2014/35/CE (150 L Boiler)
- PED art. 4.3. 2014/68/CE

COMPACT DESIGN

The compact size of our 50 litre boiler meets the needs of smaller hospitals and private clinics for an efficient space allocation. A solution for particular areas where one or two WASSENBURG® endoscope washer-disinfectors are installed. The compact boiler has the capacity to fill two WASSENBURG® washer-disinfectors basins with warm water.

The Wassenburg Boiler comes with a wall-mounted, standing and rolling configuration. The wall-mounted boiler can easily be fixed to the wall with the included back frame. The rolling boiler is a movable model with four casters. The standing and rolling boilers are provided with a Wassenburg housing which is in-line with the WASSENBURG® washer-disinfectors.



Example of configuration with WASSENBURG® washer-disinfectors.

Other configurations can be performed.

	Wall-mounted Wassenburg Boiler (50 L)	Standing and rolling Wassenburg Boiler (50 L)
Dimensions:	475 (d) x 470 (w) x 679 (h) mm	755,5 (d) x 600 (w) x 1029,5 (h) mm
Weight (empty):	27,5 kg	88,9 kg
Weight (filled):	80,9 kg	142,3 kg
Content:	53,4 litre	53,4 litre
Power:	3750 W	3750 W
Voltage:	3 x 400 VAC	3 x 400 VAC
Fuse:	3 x 10 A	3 x 10 A
Working pressure:	7 Bar*	7 Bar*
Set temperature:	85°C	85°C
Compatibility:	RO compatible	RO compatible
Capacity:	filling 2 basins of WASSENBURG® washer-disinfectors running EndoHigh® PAA & Detergent or EndoHigh® GTA & Detergent	

*Please check the full installation specifications for the performance with our WASSENBURG® washer-disinfectors.

HIGHER CAPACITY

The 150 litre Wassenburg Boiler supports hospitals with a large cleaning and disinfection capacity.

The boiler can fill up to four WASSENBURG® washer-disinfectors basins with warm water. The high capacity Wassenburg Boiler is available in a wall-mounted and standing configuration. A standing frame can be ordered separately when additional support is required. The white powder-coated steel frame provides easy access for installation and maintenance.



Example of configuration with WASSENBURG® washer-disinfectors.
Other configurations can be performed.

	Wall-mounted Wassenburg Boiler (150 L)	Standing and rolling Wassenburg Boiler (150 L)
Dimensions:	555 (d) x 555 (w) x 1297 (h) mm	760 (d) x 600 (w) x 1747 (h) mm
Weight (empty):	42,5 kg	74,4 kg
Weight (filled):	192,5 kg	224,4 kg
Content:	150 litre	150 litre
Power:	6000 W	6000 W
Voltage:	3 x 400 VAC	3 x 400 VAC
Fuse:	3 x 16 A	3 x 16 A
Working pressure:	7 Bar*	7 Bar*
Set temperature	85°C	85°C
Compatibility:	RO compatible	RO compatible
Capacity:	filling 4 basins of WASSENBURG® washer-disinfectors running EndoHigh® PAA & Detergent or 3 basins running EndoHigh® GTA & Detergent	

*Please check the full installation specifications for the performance with our WASSENBURG® washer-disinfectors.



Wassenburg Medical B.V.

Edisonring 9

6669 NA DODEWAARD

THE NETHERLANDS

T: +31 (0) 488 700 500

F: +31 (0) 488 453 685

info@wassenburgmedical.nl

www.wassenburgmedical.com